

# MOLYSLIP / RED RUBBER GREASE

**MOLYSLIP®**



## **MCC**

25g pod (pack of 6) - **M916**  
65g tube - **M816**  
450g tin - **40004**  
3kg tin - **40030**

## **MWF**

350ml bottle - **41003**  
5L pail - **41050**

## **MWS**

400ml aerosol - **42004**

MOLYSLIP® MCC, MWF and MWS is a range of high-performance lubricants designed for severe metal working operations such as drilling, reaming and tapping. They are highly concentrated mixtures of lubricity and reactive extreme-pressure and anti-wear additives.

All of the products in the range provide excellent surface finish to components and protect tooling from wear and damage.

They are suitable for most drilling, reaming and tapping (spiral point, spiral flute and fluteless) operations on most metals. For maximum flexibility of use and to accommodate individual preference the products available are:

**MCC** – A soft paste compound suitable for brush or dip application

**MWF** – A medium viscosity fluid suitable for manual application or automatic lubricator systems

**MWS** – A convenient aerosol form of MWF

**MWC** - A low melting point metalworking compound containing molybdenum disulphide

It is advised that compatibility is checked prior to use as the sulphurised, extreme-pressure additives may interact with some metals.

## **Features:**

- Excellent extreme pressure and anti-wear performance
- Maximises tool life in arduous operations
- Available in liquid, paste and aerosol form

## **Instructions:**

To obtain optimum performance MCC, MWF and MWS should be used as supplied. Apply either directly to the tool (while stationary) or to the hole to be tapped. Do not apply to rotating tooling.

**FEATURE**

## **Red Rubber Grease**



MOLYTEC RED RUBBER GREASE is a premium quality clay thickened grease formulated with castor oil. Molytec Red Rubber Grease provides outstanding performance in a wide range of applications where contact with rubber compounds is likely or required. Molytec Red Rubber Grease is recommended as a general purpose. This grease is compatible for automotive and industrial components for natural or synthetic rubber.

- Protects against rust & corrosion
- Excellent lubricity
- Compatible with natural & synthetic rubber
- Clay based

500g Tub - **M970**



## Marine Grease

Molytec Marine Grease is a No 2 NLGI lithium complex, high load carrying and superior water resistant multi-purpose grease. This product is recommended for marine trailer and other bearings that are prone to water contamination.

450g tub - **M874**  
450g cartridge - **M875**  
2.5kg pail - **M876**  
20kg drum - **M877**



## Food Machinery Grease (FMG)

A premium Aluminium Complex NLGI No 2 grease that is pure white, odourless and tasteless. Provides protection against rust and resists oxidation. Suitable for use at temperatures from -25 C to 190 C. HALAL H1. FOOD GRADE APPROVED.

450g cartridge - **M803**  
20kg drum - **M853**



## Moly-tac II Grease

Molytac 2 Grease is a high quality, multi-purpose, extreme pressure, water resistant No 2 NLGI grade grease containing 3% molybdenum disulphide. This lithium complex grease is ideal for CV joints, and has many automotive, mining and industrial bearing applications.

450g Cartridge **M820**  
2.5kg pail - **M824**  
20kg drum - **M828**



## Truck & Farm Grease

Truck & Farm Grease is a No 2 NLGI lithium complex based grease designed to give lubrication for normal to severe conditions. It is suitable for use in wheel bearings on vehicles fitted with disc brakes, where high temperatures cause ordinary greases to soften and give ineffective lubrication.

450g cartridge - **M870**  
2.5kg pail - **M872**  
20kg drum - **M873**