



Countersunk / Splined / Metric

Low profile head. Optimal for low load bearing application in thin sheet. Dimensioned for installation into hard metric holes. Splined body improves torque-to-turn resistance.

Material: Aluminium alloy (2.5% Mg) to AA 5052

Finish: Chemically brightened



Thread Size	SKU	Grip Range mm	Hole Size mm	A mm	B mm	C mm	D mm	Pull-Out KN	Push-Out KN	Torque-To-Turn* Nm
M3*	43CA3SM	0.5-1.5	5.0	4.95	9.0	6.0	0.5	1.0	0.6	2.0
M4	43CA4SP	0.8-2.5	6.0	5.95	11.0	7.0	0.5	2.6	0.9	3.4
	43CA4SP2	2.5-3.5	6.0	5.95	12.0	7.0	0.5	2.6	0.9	3.4
M5	43CA5SP	0.8-2.5	7.0	6.95	12.0	8.0	0.5	4.4	1.5	6.9
	43CA5SP2	2.5-3.5	7.0	6.95	13.0	8.0	0.5	4.4	1.5	6.9
M6	43CA6SP	1.0-2.5	9.0	8.95	14.0	10.0	0.5	4.9	2.9	13.7
	43CA6SP2	2.5-4.0	9.0	8.95	15.5	10.0	0.5	4.9	2.9	13.7
M8	43CA8SP	1.0-2.5	11.0	10.95	15.5	12.0	0.7	10.8	3.2	25.5
	43CA8SP2	2.5-4.0	11.0	10.95	17.0	12.0	0.7	10.8	3.2	25.5
M10	43CA10SP	1.0-2.5	13.0	12.95	16.0	14.0	0.7	11.8	3.6	44.1

* Smooth body

Torque-To-Turn *

Minimum torque applied to cause the fastener to turn in the parent material.

Dimensions and specifications are subject to change without notice.

The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses.

We recommend testing your application when an exact strength figure is required or the load to be applied comes close to the published data.

