



Countersunk / Splined / Metric

Low profile head. Optimal for low load bearing applications in thin sheet. Dimensioned for installation into hard metric holes. Splined body improves torque-to-turn resistance.

Material: G304 Stainless Steel



Thread Size	SKU	Grip Range mm	Hole Size mm	A mm	B mm	C mm	D mm	Pull-Out KN	Push-Out KN	Torque-To-Turn* Nm
M3	43CS3SP	0.5-2.0	5.0	4.95	9.0	6.0	0.5	5.3	2.7	3.4
M4	43CS4SP	0.5-2.5	6.0	5.95	11.0	7.0	0.5	9.8	2.9	4.9
	43CS4SP2	2.5-4.0	6.0	5.95	12.5	7.0	0.5	9.8	2.9	4.9
M5	43CS5SP	0.5-3.0	7.0	6.95	12.0	8.0	0.5	15.7	2.9	8.8
	43CS5SP2	3.0-4.5	7.0	6.95	13.5	8.0	0.5	15.7	2.9	8.8
M6	43CS6SP	0.5-3.0	9.0	8.95	14.0	10.0	0.5	20.6	2.9	15.7
	43CS6SP2	3.0-5.0	9.0	8.95	16.0	10.0	0.5	20.6	2.9	15.7
M8	43CS8SP	0.5-3.0	11.0	10.95	16.0	12.0	0.5	29.4	3.9	29.4
	43CS8SP2	3.0-5.5	11.0	10.95	18.5	12.0	0.5	29.4	3.9	29.4
M10	43CS10SP	1.0-3.5	13.0	12.95	19.0	14.2	0.8	42.2	5.9	39.2
	43CS10SP2	3.5-6.0	13.0	12.95	21.5	14.2	0.8	42.2	5.9	39.2

Torque-To-Turn *

Minimum torque applied to cause the fastener to turn in the parent material.

Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet.

The test data provides approximate strength values averaged in multiple tests in various materials and thicknesses.

We recommend testing your application when an exact strength figure is required, or the load to be applied comes close to the published data.

