

Self Drilling Metal Screw

Head Style: Countersunk Head


Drive Type: Phillips

Material: Hardened Steel

Class Grade: Class 3 / 4 / B8

Finish: Galvanised

Corrosion Protection Level: Excellent



*CAD drawings shown for graphic representation only.**

Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Drill Point Length (P) (mm)	Min To Max Steel Thickness (mm)		Driver Bit Size (AS)	sku (qfind)
			Min	Max	Min	Max	Nom	Nom	Min	Max	Nom	
8g (4.20mm)	18	Coarse	4.00	4.20	7.70	8.10	3.45	7.00	0.75	2.50	PH2	08C81825C3
10g (4.80mm)	16	Coarse	4.65	4.80	8.80	9.20	4.45	7.00	1.20	3.50	PH2	08C1016C3
10g (4.80mm)	24	Fine	4.65	4.80	8.80	9.20	4.45	7.00	1.20	5.00	PH2	08CC31024

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024