## Flange Serrated Nut

**Thread Type**: Metric - Coarse **Thread Direction**: Right Hand


Material: Carbon Steel


Class Grade: High Tensile Class 8


Finish: Zinc Plated

Corrosion Protection Level: Moderate

Standard: DIN 6923







Cad Drawings shown for graphic representation only.\*

Size	Thread Pitch (mm)	Thread Type	Overall Nut Height (B) (mm)		Flange Diameter (F) (mm)		Across Flats (AF) (mm)		Spanner Size (AF)	sku (Part Number)
			Min	Max	Min	Max	Min	Max	(mm)	(Fait Nullibel)
M3	0.50mm	Coarse	3.55	3.75	7.50	7.90	5.32	5.50	5.5mm	41FL3
M4	0.70mm	Coarse	4.35	4.65	9.60	10.00	6.78	7.00	7mm	41FL4
M5	0.80mm	Coarse	4.70	5.00	11.50	11.90	7.78	8.00	8mm	41FL5
M6	1.00mm	Coarse	5.64	6.00	12.70	13.30	9.78	10.00	10mm	41FL6
M8	1.25mm	Coarse	7.60	8.00	16.50	17.30	12.73	13.00	13mm	41FL8
M10	1.50mm	Coarse	9.60	10.00	20.50	21.30	14.73	15.00	15mm	41FL10
M12	1.75mm	Coarse	11.60	12.00	24.60	25.80	17.73	18.00	18mm	41FL12
M16	2.00mm	Coarse	15.30	16.00	33.80	35.00	23.67	24.00	24mm	41FL16

## Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and con

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

\* Cad Drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved

Version: 25 Aug 2024