BOLT&NUT AUSTRALIA | Fasteners | FASTENER | FKO |

w: boltandnut.com.au | e: sales@boltandnut.com.au | p: 07 3192 9800

Allthread

Thread Type: Metric Coarse - Left Hand Thread Thread Direction: Left Hand Material Finish: Plain Black Uncoated Corrosion Protection Level: Poor Standard: DIN 975

(L) (D)

CAD drawings shown for graphic representation only.*

Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Allthread Length (L) (mm)	Class Grade	sku (ofind)
			Min	Max	Nom		(qfind)
M6	1.00	Left Hand Thread	5.52	6.48	1000	Low Tensile Class 4.6	54LH61P
M8	1.25	Left Hand Thread	7.42	8.58	1000	Low Tensile Class 4.6	54LH81P
M10	1.50	Left Hand Thread	9.42	10.58	1000	Low Tensile Class 4.6	54LH101P
M12	1.75	Left Hand Thread	11.30	12.70	1000	Low Tensile Class 4.6	54LH121P
M16	2.00	Left Hand Thread	15.30	16.70	1000	Low Tensile Class 4.6	54LH161P
M20	2.50	Left Hand Thread	19.67	20.00	1000	Low Tensile Class 4.6	54LH201P
M24	3.00	Left Hand Thread	23.67	24.00	1000	Low Tensile Class 4.6	54LH241P
M42	4.50	Left Hand Thread	41.44	41.94	1000	Low Tensile Class 4.6	54LH421P

Disclaimer:

Dimensional data and technical information was obtained from publically available

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only;

where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024