Hex Head Bolt

Thread Type: UNC / BSW - Coarse Thread Direction: Right Hand


Material: Carbon Steel


Class Grade: High Tensile Grade 8

Finish: Zinc Plated

Corrosion Protection Level: Moderate

Standard: AS2465-1999





CAD drawings shown for graphic representation only.*

Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Height (H) (mm)		Across Flats (AF) (mm)		Spanner Size (AF)	sku (offinal)
			Min	Max	Min	Max	Min	Max	(inches)	(qfind)
1/4"	20	Coarse	6.15	6.33	3.81	4.15	10.80	11.13	7/16	51C14
5/16"	18	Coarse	7.78	7.93	4.96	5.36	12.30	12.70	1/2	51C516
3/8"	16	Coarse	9.38	9.53	5.75	6.18	13.82	14.28	9/16	51C38
7/16"	14	Coarse	10.93	11.13	6.91	7.40	15.55	15.88	5/8	51C716
1/2"	13	Coarse	12.53	12.70	7.70	8.21	18.70	19.05	3/4	51C12
9/16"	12	Coarse	14.08	14.28	8.84	9.43	20.27	20.63	13/16	51C916
5/8"	11	Coarse	15.68	15.88	9.61	10.24	23.42	23.83	15/16	51C58
3/4"	10	Coarse	18.83	19.05	11.56	12.27	27.94	28.58	1-1/8	51C34
7/8"	9	Coarse	21.85	22.36	13.49	14.30	32.64	33.32	1-5/16	51C78
1"	8	Coarse	25.15	25.40	15.02	15.93	37.32	38.10	1-1/2	51C1
urces and not nere discrepar akes no warra ontact the rele	t acquired through standard agen ncies are found they are subject to anties or representations regarding evant standard authorities for acc	sobtained from publically availabl cies. It has been completed and o o change without notice. Bolt & No o the accuracy and validity of the courate and detailed information.	ompiled for reference purp ut Australia	•		4/	A		© Bolt & Nut Australia Pty Lt	d. All rights reserv Version: 18 Mar 2

^{*} CAD drawings may not reflect diameter, thread length or overall length.