(A) (L) (CA) (CA) (D) (AS) (H) (TPI)

Cad Drawings shown for graphic representation only.*

Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	Countersunk Angle	Driver Bit Size (AS)	sku (Part Number)
			Min	Max	Min	Max	Nom			(Fait Number)
M3	0.50mm	Coarse	2.87	2.98	5.60	6.72	1.86	90°	T10	21CTS3
M4	0.70mm	Coarse	3.83	3.97	7.53	9.20	2.48	90°	T20	21CTS4
M5	0.80mm	Coarse	4.82	5.00	9.43	10.00	3.10	90°	T25	21CTS5
M6	1.00mm	Coarse	5.82	6.00	11.34	12.00	3.72	90°	Т30	21CTS6
M8	1.25mm	Coarse	7.78	8.00	15.24	16.00	4.96	90°	T45	21CTS8

Disclaimer:

Dimensional data and technical information was obtained from publically available

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* Cad Drawings may not reflect diameter, thread length or overall length.

Machine Screw

Drive Type: Torx

Head Style: Countersunk Head

Thread Type: Metric - Coarse

Corrosion Protection Level: Excellent

Material: Stainless Steel Class Grade: A2-70 G304

Standard: ISO10642

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 29 Aug 2024