

Hose Clamp


Clamp Style: Worm Drive Perforated

Material: Stainless Steel

Class Grade: A2-70 G304

Corrosion Protection Level: Excellent

Standard: DIN 3017



*Cad Drawings shown for graphic representation only.**

Clamp Range (S) (mm)	Band Width (B) (mm)	Clamp Width MAX (A) (mm)	sku (Part Number)
10mm to 16mm	9	14.00	74HCS10169I
12mm to 22mm	9	14.00	74HCS12229I
16mm to 27mm	9	14.00	74HCS16279I
18mm to 32mm	9	14.20	74HCS1832127E
20mm to 32mm	9	14.00	74HCS20329I
25mm to 40mm	9	14.00	74HCS25409I
30mm to 45mm	9	14.00	74HCS30459I
35mm to 50mm	9	14.00	74HCS35509I
40mm to 60mm	9	14.00	74HCS40609I
50mm to 70mm	9	14.00	74HCS50709I
60mm to 80mm	12	20.00	74HCS608012I
70mm to 90mm	12	20.00	74HCS709012I
80mm to 100mm	12	20.00	74HCS8010012I
90mm to 110mm	12	20.00	74HCS9011012I
100mm to 120mm	12	20.00	74HCS10012012I
110mm to 130mm	12	20.00	74HCS11013012I

Clamp Range (S) (mm)	Band Width (B) (mm)	Clamp Width MAX (A) (mm)	sku (Part Number)
120mm to 140mm	12	20.00	74HCS12014012I

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

* Cad Drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 07 May 2024