
Spring Hook with Eye

Material: Stainless Steel Class Grade: A4-70 G316

Corrosion Protection Level: Ultimate



CAD drawings shown for graphic representation only.*

Size	Length L (1) (mm)	Width (A) (mm)		Inside Small Eye (W) (mm)		Inside Large Eye (C) (mm)		Width Of Spring Opening (E) (mm)		Breaking Load	sku (qfind)
	Nom	Min	Max	Min	Max	Min	Max	Min	Max	Nom	(qiiila)
4mm	40.00	19.80	20.20	4.50	4.60	12.40	12.60	3.60	3.80	-	62SPHSE440M
5mm	50.00	24.80	25.20	6.20	6.30	15.40	15.60	6.10	6.30	220	62SPHSE550M
6mm	60.00	29.80	30.20	7.05	7.15	18.40	18.60	8.50	8.70	272	62SPHSE660M
8mm	80.00	39.80	40.20	9.75	9.95	25.60	25.80	8.90	9.10	508	62SPHSE880M
10mm	100.00	49.80	50.20	13.30	13.50	31.40	31.60	14.70	14.90	728	62SPHSE10100M
11mm	120.00	59.80	60.20	15.80	16.00	37.40	37.60	17.20	17.40	7 -	62SPHSE11120M

Disclaimer:

 $\label{thm:constraint} \mbox{Dimensional data and technical information was obtained from publically available}$

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only;

where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024