Flange Serrated Nut

Thread Type: Metric - Coarse Thread Direction: Right Hand


Material: Carbon Steel


Class Grade: High Tensile Class 8

Finish: Zinc Plated

Corrosion Protection Level: Moderate

Standard: DIN 6923





CAD drawings shown for graphic representation only.*

Size	Thread Pitch (mm)	Thread Type	Overall Nut Height (B) (mm)		Flange Diameter (F) (mm)		Across Flats (AF) (mm)		Spanner Size (AF) (mm)	sku (afind)
			Min	Max	Min	Max	Min	Max	(11111)	(qfind)
M3	0.50	Coarse	3.55	3.75	7.50	7.90	5.32	5.50	5.5	41FL3
M4	0.70	Coarse	4.35	4.65	9.60	10.00	6.78	7.00	7	41FL4
M5	0.80	Coarse	4.70	5.00	11.50	11.90	7.78	8.00	8	41FL5
M6	1.00	Coarse	5.64	6.00	12.70	13.30	9.78	10.00	10	41FL6
M8	1.25	Coarse	7.60	8.00	16.50	17.30	12.73	13.00	13	41FL8
M10	1.50	Coarse	9.60	10.00	20.50	21.30	14.73	15.00	15	41FL10
M12	1.75	Coarse	11.60	12.00	24.60	25.80	17.73	18.00	18	41FL12
M16	2.00	Coarse	15.30	16.00	33.80	35.00	23.67	24.00	24	41FL16

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only;

where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved

Version: 18 Mar 2024