Flange Serrated Nut

Thread Type: UNC / BSW - Coarse Thread Direction: Right Hand


Material: Carbon Steel


Class Grade: High Tensile Grade 5


Finish: Zinc Yellow

Corrosion Protection Level: Moderate

Standard: IFI 145 / B18 2.2







CAD drawings shown for graphic representation only.*

Size	Thread Pitch (TPI)	Thread Type	Overall Nut Height (B) (mm)		Hex Height (H) (mm)	Flange Diameter (F) (mm)		Across Flats (AF) (mm)		Spanner Size (AF) (inches)	sku (qfind)
			Min	Max	Nom	Min	Max	Min	Max	(mones)	(qiilid)
1/4"	20	Coarse	5.64	6.00	3.81	14.58	15.09	10.88	11.16	7/16	41FLC14ZY
5/16"	18	Coarse	6.55	7.37	4.32	16.77	17.28	12.43	12.76	1/2	41FLC516ZY
3/8"	16	Coarse	8.38	8.81	5.85	18.50	19.05	14.00	14.28	9/16	41FLC38ZY
7/16"	14	Coarse	9.50	10.00	5.67	23.10	23.80	17.15	17.48	11/16	41FLC716ZY
1/2"	13	Coarse	11.10	11.63	7.88	25.40	26.19	18.70	19.00	3/4	41FLC12ZY

Disclaimer:

Dimensional data and technical information was obtained from publically available

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only;

where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024

^{*} CAD drawings may not reflect diameter, thread length or overall length.