


Standard Full Nut

BOLT&NUT

Thread Type: Metric - Coarse Thread Direction: Right Hand Material: Nylon Class Grade: Low Tensile Class 4.6 Finish: White Corrosion Protection Level: Excellent Standard: DIN 934

AUSTRALIA | Fasteners | FASTENER | FKO |



Cad Drawings shown for graphic representation only.*

Size	Thread Pitch (mm)	Thread Type	Overall Nut Height (B) (mm)		Across Flats (AF) (mm)		Spanner Size (AF)	sku (Part Number)
			Min	Max	Min	Max	(mm)	(Fait Number)
M2	0.40mm	Coarse	1.35	1.75	3.82	4.00	4mm	41NY2
M2.5	0.45mm	Coarse	1.75	2.00	4.82	5.00	5mm	41NY25
M3	0.50mm	Coarse	2.15	2.40	5.32	5.50	5.5mm	41NY3
M4	0.70mm	Coarse	2.90	3.30	6.78	7.00	7mm	41NY4
M5	0.80mm	Coarse	3.70	4.00	7.78	8.00	8mm	41NY5
M6	1.00mm	Coarse	4.70	5.00	9.78	10.00	10mm	41NY6
M8	1.25mm	Coarse	6.14	6.40	12.73	13.00	13mm	41NY8
M10	1.50mm	Coarse	7.42	8.00	16.73	17.00	17mm	41NY10
M12	1.75mm	Coarse	9.64	10.00	18.67	19.00	19mm	41NY12
M16	2.00mm	Coarse	12.30	13.00	23.67	24.00	24mm	41NY16
M20	2.50mm	Coarse	15.00	16.00	29.16	30.00	30mm	41NY20

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* Cad Drawings may not reflect diameter, thread length or overall length.

Version: 25 Aug 2024