
Standard Full Nut Thread Type: UNC / BSW - Coarse

Thread Direction: Right Hand Material: Stainless Steel Class Grade: A2-70 G304 Corrosion Protection Level: Excellent Standard: ANSI B18.6.3 Comments: UNC and BSW have the same thread per inch value, except for 1/2"



Cad Drawings shown for graphic representation only.*

Size	Thread Pitch (TPI)	Thread Type	Overall Nut Height (B) (mm)		Across Flats (AF) (mm)		Spanner Size (AF)	sku (Port Number)
			Min	Max	Min	Max	(inches)	(Part Number)
1/4"	20 TPI	Coarse	5.39	5.75	10.88	11.16	7/16"	41SC14
5/16"	18 TPI	Coarse	6.56	6.94	12.43	12.76	1/2"	41SC516
3/8"	16 TPI	Coarse	8.13	8.56	14.00	14.28	9/16"	41SC38
7/16"	14 TPI	Coarse	9.28	9.78	17.15	17.48	11/16"	41SC716
1/2"	13 TPI	Coarse	10.85	11.38	18.70	19.05	3/4"	41SC12
9/16"	12 TPI	Coarse	12.02	12.60	21.87	22.23	7/8"	41SC916
5/8"	11 TPI	Coarse	13.59	14.20	23.42	23.83	15/16"	41SC58
3/4"	10 TPI	Coarse	15.68	16.90	27.64	28.58	1-1/8"	41SC34
7/8"	9 TPI	Coarse	18.39	19.72	32.24	33.33	1-5/16"	41SC78
1"	8 TPI	Coarse	21.11	22.53	36.83	38.16	1-1/2"	41SC1
rces and not a ere discrepanc kes no warrant ntact the releva	ies are found they are subject to cha	It has been completed and compiled ange without notice. Bolt & Nut Austra accuracy and validity of the compiled and detailed information.	lia		1	A	© Bolt & N	ut Australia Ry Ltd. All rights res Version: 25 Au

* Cad Drawings may not reflect diameter, thread length or overall length.