
Nyloc Insert Nut

BOLT&NUT

Thread Type: UNF - Fine Thread Direction: Right Hand Material: Stainless Steel Class Grade: A4-70 G316 Corrosion Protection Level: Ultimate Standard: NE Series



Cad Drawings shown for graphic representation only.*

Size	Thread Pitch (TPI)	Thread Type	Overall Nut Height (B) (mm)		Hex Height (H) (mm)	Across Flats (AF) (mm)		Spanner Size (AF) (inches)	sku (Part Number)
			Min	Max	Nom	Min Max (inclus)	(inches)	(rait number)	
1/4"	28 TPI	Fine	7.55	8.35	5.72	10.88	11.16	7/16"	41NSF14M
5/16"	24 TPI	Fine	8.35	9.10	6.35	12.43	12.76	1/2"	41NSF516M
3/8"	24 TPI	Fine	11.10	11.90	8.51	14.00	14.28	9/16"	41NSF38M
7/16"	20 TPI	Fine	11.10	11.90	8.23	15.55	15.88	5/8"	41NSF716M
1/2"	20 TPI	Fine	14.70	15.45	11.79	18.70	19.05	3/4"	41NSF12M
5/8"	18 TPI	Fine	18.67	20.00	15.07	23.42	23.83	15/16"	41NSF58M
3/4"	16 TPI	Fine	21.80	22.60	18.90	26.73	27.03	1-1/8"	41NSF34M
1"	12 TPI	Fine	25.70	27.40	20.96	36.25	36.58	1-1/2"	41NSF1M

Disclaimer:

Dimensional data and technical information was obtained from publically available

sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only;

Galore FASTENER FKO

where discrepancies are found they are subject to change without notice. Bolt & Nut Australia

makes no warranties or representations regarding the accuracy and validity of the compiled information and data.

Contact the relevant standard authorities for accurate and detailed information.

* Cad Drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved

Version: 25 Aug 2024