
Countersunk Head Nutsert

Body Type: Round Closed **Outside Body**: Smooth

Thread Type: Metric - Coarse Body Material: Stainless Steel Class Grade: A2-70 G304

Finish: Stainless Steel A2-70 G304 Corrosion Protection Level: Excellent



CAD drawings shown for graphic representation only.*

Size	Thread Pitch (mm)	Thread Type	Material Grip Range (G) (mm)		Overall Nut Height (B) (mm)	Head Diameter (C) (mm)	Nut Width (A) (mm)	Flange Thickness (H) (mm)	Recommended Hole Size (mm)	Pull Out (KN)	Push Out (KN)	Torque To Turn (NM)	sku (qfind)
			Min	Max	Nom	Nom	Nom	Nom	Nom	Nom	Nom	Nom	
M4	0.70	Coarse	0.50	2.50	16.00	7.00	5.90	0.50	6.00	7	2	4	43CCES4SM
M5	0.80	Coarse	0.50	3.00	18.00	8.00	6.90	0.50	7.00	12	2	9	43CCES5SM
M6	1.00	Coarse	0.50	3.00	21.00	10.00	8.90	0.50	9.00	20	4	14	43CCES6SM
M8	1.25	Coarse	0.50	3.00	23.50	12.00	10.90	0.50	11.00	32	4	44	43CCES8SM

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024