

## Batten Timber Screw

**Head Style:** Bugle Head

**Drive Type:** Square


**Screw Point:** Type 17 for Timber

**Material:** Stainless Steel

**Class Grade:** A4-70 G316

**Corrosion Protection Level:** Ultimate

**Internal External:** External



*Cad Drawings shown for graphic representation only.\**

Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Driver Bit Size (AS)	sku (Part Number)
			Min	Max	Min	Max	Min	Max		
6g (3.50mm)	10 TPI	Coarse	3.40	3.50	6.50	6.80	3.70	3.90	SQ1	06BUSS61025M
8g (4.20mm)	10 TPI	Coarse	4.00	4.20	7.80	8.00	4.10	4.30	SQ2	06BUSS81025M
10g (4.80mm)	10 TPI	Coarse	4.65	4.80	9.40	9.60	4.10	4.30	SQ2	06BUSS101050M
12g (5.50mm)	10 TPI	Coarse	5.30	5.40	9.60	10.00	4.40	4.60	SQ3	06BUSS121058M
14g (6.30mm)	10 TPI	Coarse	6.20	6.40	12.00	12.20	5.30	5.50	SQ3	06BUSS14M

**Disclaimer:**

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

\* Cad Drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 21 Aug 2024