

## Wood Screw


**Head Style:** Countersunk Head

**Drive Type:** Phillips

**Material:** Stainless Steel

**Class Grade:** A2-70 G304

**Corrosion Protection Level:** Very Good



*CAD drawings shown for graphic representation only.\**

Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Driver Bit Size (AS)	sku (qfind)
			Min	Max	Min	Max	Min	Max	Nom	
4g (2.90mm)	24	Coarse	2.74	2.90	5.25	5.50	1.35	1.55	PH1	07CS4
6g (3.50mm)	18	Coarse	3.40	3.50	6.45	6.80	1.70	2.00	PH2	07CS634
8g (4.20mm)	15	Coarse	4.00	4.20	7.80	8.10	2.05	2.35	PH2	07CS834
10g (4.80mm)	12	Coarse	4.65	4.80	9.00	9.50	2.40	2.70	PH2	07CS10112
12g (5.50mm)	11	Coarse	5.30	5.40	10.40	11.00	2.75	3.05	PH3	07CS12114
14g (6.30mm)	10	Coarse	6.20	6.40	11.70	12.40	3.10	3.50	PH3	07CS14

**Disclaimer:**

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

\* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024