

Wood Screw


Head Style: Countersunk Head

Drive Type: Slot

Material: Solid Brass

Class Grade: Low Tensile Class 4.6

Corrosion Protection Level: Ultimate



*CAD drawings shown for graphic representation only.**

Size	Thread Pitch (TPI)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)	sku (qfind)
			Min	Max	Min	Max	Nom	
2g (2.20mm)	26	Coarse	2.08	2.24	3.70	4.40	1.30	07CSLB2
3g (2.50mm)	24	Coarse	2.30	2.50	4.30	5.10	1.50	07CSLB3
4g (2.90mm)	22	Coarse	2.74	2.90	5.00	5.70	1.70	07CSLB4
6g (3.50mm)	18	Coarse	3.40	3.50	6.20	7.00	2.10	07CSLB6
8g (4.20mm)	15	Coarse	4.00	4.20	7.40	8.40	2.50	07CSLB8
10g (4.80mm)	13	Coarse	4.65	4.80	8.60	9.80	2.90	07CSLB10
12g (5.50mm)	11	Coarse	5.30	5.40	11.50	12.90	3.40	07CSLB12

Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024