
## **Socket Allen Screw**

Head Style: Low Head Cap Drive Type: Internal Hex Thread Type: Metric - Coarse Material: Alloy Steel Heat Treated Class Grade: High Tensile Class 10.9

Finish: Plain Black Uncoated

Corrosion Protection Level: Poor

Standard: DIN 7984



CAD drawings shown for graphic representation only.\*

Size	Thread Pitch (mm)	Thread Type	Product Diameter (D) (mm)		Head Diameter (A) (mm)		Head Height (H) (mm)		Driver Bit Size (AS) (mm)	sku (afin d)
			Min	Max	Min	Max	Min	Max	Nom	(qfind)
МЗ	0.50	Coarse	2.87	2.98	5.32	5.50	1.86	2.00	2	31L3P
M4	0.70	Coarse	3.83	3.97	6.78	7.00	2.66	2.80	2	31L4P
M5	0.80	Coarse	4.82	5.00	8.28	8.50	3.32	3.50	3	31L5P
M6	1.00	Coarse	5.82	6.00	9.78	10.00	3.82	4.00	4	31L6P
M8	1.25	Coarse	7.78	8.00	12.73	13.00	4.82	5.00	5	31L8P
M10	1.50	Coarse	9.78	10.00	15.73	16.00	5.82	6.00	7	31L10P
M12	1.75	Coarse	11.73	12.00	17.73	18.00	6.78	7.00	8	31L12P
M16	2.00	Coarse	15.73	16.00	23.73	24.00	8.78	9.00	12	31L16P

## Disclaimer:

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

\* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 19 Mar 2024