

## HSFG Structural K0 Washer

**Material:** High Tensile Steel 35-41 HRC


**Class Grade:** High Tensile Class 8.8

**Corrosion Protection Level:** Excellent

**Finish:** Galvanised

**Standard:** K0 AS1252:2016

**System Of Measurement:** Metric



*CAD drawings shown for graphic representation only.\**

Industry Size (mm)	Inside Dimension (ID) (mm)		Outside Dimension (OD) (mm)		Thickness (T) (mm)		sku (qfind)
	Min	Max	Min	Max	Min	Max	
12	13.30	14.00	25.70	27.70	3.10	3.90	71G12GK0
16	17.30	18.00	32.40	34.40	3.10	3.90	71G16GK0
20	21.00	22.00	37.40	39.40	3.10	3.90	71G20GK0
22	24.00	25.00	42.40	44.40	3.30	3.90	71G22GK0
24	26.30	27.30	48.40	50.40	3.30	3.90	71G24GK0
27	30.50	31.60	54.10	56.60	3.30	3.90	71G27GK0
30	33.50	34.50	58.10	60.10	3.30	3.90	71G30GK0
33	36.50	37.50	64.10	66.60	3.30	3.90	71G33GK0
36	39.00	40.00	70.10	72.80	3.30	3.90	71G36GK0

**Disclaimer:**

Dimensional data and technical information was obtained from publically available sources and not acquired through standard agencies. It has been completed and compiled for reference purposes only; where discrepancies are found they are subject to change without notice. Bolt & Nut Australia makes no warranties or representations regarding the accuracy and validity of the compiled information and data. Contact the relevant standard authorities for accurate and detailed information.

\* CAD drawings may not reflect diameter, thread length or overall length.

© Bolt & Nut Australia Pty Ltd. All rights reserved.

Version: 18 Mar 2024